SWS - Forms in the Maintenance Menu - Configuration

Last Modified on 08/07/2024 3:30 pm EDT

The Configuration screen displays the configuration for various Manitou-related servers and applications.

Manitou Configuration will be defined on your system before installation, but users may find it necessary to modify it themselves at a later time.

Adding a Server to Manitou

Perform the following steps to add a server to Manitou:

1. Navigate to the Maintenance menu, click "Setup" then click "Configuration".

Result: The "Configuration" form displays as shown in the following screenshot:

View	New	Edit	Delete	Save	Cancel
Configuration					
	System	Description:	Notes:	Add	1
VQ	System 1	System 1			-
		Disabled		Beng	ve.
Ado	Bemove				
C					
	Server list only C Sta w unused servers	art order			
1 510	w unused servers				
🖁 Manitou		-			
SysConf	'System 1'				
E- Serv					
	DEV-11				
P	Applications				
	ACG on DEV-11				
	Ports				
	DEV-12				
61	Applications				
	(DEV-12)				
	Ports				
	DEV-LAB1				
ē	Applications				
	ACG DEV-LAB1				
	Ports				
e 😫	MANITOU161B				
P	Applications				
	Media Gateway				
	Telephony Server				
	Ports MANITOU161e				
	Annications	-			

- 2. Click "Edit".
- 3. Select the server icon in the Navigation Window and click "Add".

Result: The "Add Server" window displays as shown in the following screenshot:

Add Server		
Machine Name:		
IP Address:		
IP Address 2:		
Existing Device:	•	
	ОК	Cancel

- 4. Enter the server name into the "Machine Name:" field.
- 5. Enter the IP addresses into the appropriate fields.

Note: If you do not already have it, obtain this information from the Central Station's IT personnel.

6. If your new server needs to be linked to an existing device, select it from the "Existing Device:" dropdown menu, and click "OK".

Result: Your new server now displays in the list.