

# SWS - Tools Menu - Options - Contact Point Device Defaults

The **Contact Point Device Defaults** Options link to the specific values related to add-on features related to contact points (phone numbers, email addresses, etc.).

## AutoText

The AutoText options define where, what, and how to send messages through AutoText for SMS messages.

- **AutoText Default Output Device Type** - This option defines the default Output Device Type for AutoText. Your choices are: "APCO-ALARM" and "MEDIAGATEWAY".
  - **APCO-ALARM** - Uses the APCO-ALARM pathway to send AutoText messages.
  - **MEDIAGATEWAY** - Uses the Manitou MediaGateway to send AutoText messages.
- **AutoText Default Script Message** - This option defines the default script text for AutoText.
  - See [Script Messages](#) for instructions for creating the AutoText script message for use here.
- **AutoText Default Service Provider Device** - This option defines the default Service Provider Device for AutoText. Your choices are: "APCO-ALARM", "AUTOSIM", "AUTOTEXT", and "OPENVOICE". The support/installation team helps determine which value you need.

## OpenVoice

The OpenVoice options determine the where, what, and how to send Text-to-voice messages.

- **OpenVoice Default Output Device Type** - This option defines the default Output Device Type for OpenVoice. Your choices are: "APCO-ALARM" and "MEDIAGATEWAY".
    - **APCO-ALARM** - Uses the APCO-ALARM pathway to send AutoText messages.
    - **MEDIAGATEWAY** - Uses the Manitou MediaGateway to send AutoText messages.
  - **OpenVoice Default Script Message** - This option defines the default script text for OpenVoice.
    - See [Script Messages](#) for instructions for creating the default script message used for OpenVoice.
  - **OpenVoice Default Service Provider Device** - This option defines the default Service Provider Device for OpenVoice. Your choices are: "APCO-ALARM", "AUTOSIM", "AUTOTEXT", and "OPENVOICE".
-